

## APPLICATION



Special primer for Raychem Reflecta plates to allow the application of a standard adhesive for ceramic tiles and natural stones.

Raychem Reflecta-P-Fix primer is a specially formulated primer designed to enable the bonding of standard tile adhesives to non-porous smooth finishes. Perfect for the installation of ceramic tile or natural stone flooring onto the aluminum layer of Reflecta plates.

Reflecta-P-Fix Primer is a ready to use solvent-free acrylic based solution which dries as plastic film.

## TECHNICAL DATA

|                         |   |
|-------------------------|---|
| Material                | Special acrylic based solution  |
| Solvents                | None  |
| Colour                  | Blue  |
| Consistency             | Liquid  |
| Consumption             | 150 g/m <sup>2</sup><br>Sufficient for approx. 18 m <sup>2</sup> Reflecta |
| Mix ratio               | Apply undiluted   |
| Dry time when applied   | Approx. 1-3 h depending on ambient temperature                            |
| Application temperature | Min. +5°C, max. +30°C   |
| Density                 | 1,3 kg/l  |
| Temperature exposure    | With floor heating max. +50°C   |
| Tool for application    | Roller, brush   |
| Liquid cleaning method  | Water   |
| Packaging               | 3 kg bucket   |

### Storage

- Dry, cool but frost free
- Shelf life 12 months (manufacturing date printed on the packaging lid)
- Use contents within a few days once open

### Disposal

- Dispose of using local regulations

## SYSTEM REFERENCES

---

- Reflecta-Insulation plates (see technical datasheet EU1727)
- Reflecta-A-Fix Adhesive (see technical datasheet CDE0745)

## REFLECTA PLATE PREPARATION

---

| Product name   | Part Number | Description   |
|----------------|-------------|---|
| Reflecta-P-Fix | 1244-020806 | Primer for the aluminium layer of the Reflecta plates to apply standard natural stone or tile adhesive: 3 kg bucket for 18m <sup>2</sup> . Consumption: 150g/m <sup>2</sup> |

- The aluminium surface of Reflecta must be clean, level and dry. Reflecta plates are to be glued to the subfloor or fixed by screws.
- Furthermore, the plates have to be free of dust, dirt, oil, grease and loose particles. The T2Red heating cable is to be laid in the grooves of the Reflecta plates before the Reflecta-P-Fix is applied.

## USAGE INSTRUCTION

---

- Stir Reflecta-P-Fix Primer before use.
- Apply the primer thinly with a flat wall brush, water brush, ceiling brush or short floor roller to achieve a uniform coating. Avoid forming pools.
- After allowing approx. 1-3 hours to dry, ceramic floors and natural stone floors can be laid using any\* flexible tile adhesive (\*in quality class C2 according to BS EN 12004 appropriate for floor heating).
- Clean tools in water immediately after use.

## NOTES

---

- All provided figures are approximate values and are subject to change depending on ambient conditions. Read and follow the product data sheets for all relevant Raychem products. Reflecta-P-Fix Primer is not for use in areas permanently under water.

## COMPATIBILITY AND THE ENVIRONMENT

---

- GISCODE D1
- To prevent accidents and safeguard health, please read and follow measures documented in the safety data sheet and product labelling.

### Europe, Middle East, Africa, India

Tel +32 16 213 511  
Fax +32 16 213 604  
info@chemelex.com

**chemelex**  
excellence is everything

**Raychem Tracer Pyrotenax Nuheat**