

## EM2-MI cable

### DESCRIPTION



Raychem EM2-MI is a constant output heating cable for simple, fast, and effective ramp and accessway heating to prevent snow and ice formation.

The pre-terminated EM2-MI cable comes complete with 3 m cold leads at each end of the heater, removing the need for on-site termination activities. Simply install the heater over the required area and connect the cold leads to the junction box and "Smart" control unit.

The EM2-MI heating cable is designed for installation in high temperature applications. The product can be installed directly under hot-poured asphalt followed by mechanical high pressure roller.

### ADVANTAGES

#### Design phase

- Simple design.
- Variable power output dependent upon cable spacing (up to 300 W/m<sup>2</sup>)
- Variety of sizes available to meet project requirements.

#### Installation phase

- Pre-terminated heating mat requires no onsite cold lead or end seal connections.
- Heating cable can be fixed to an existing reinforcement bar or with fixing strips from Chemelex.
- Extremely robust and resistant to installation damage.

#### The applications

- Excellent for irregular shaped areas.
- Vehicle accessways and loading bays.
- Applications under hot-poured asphalt.
- Suitable for the mechanical processing of mastic asphalt and road asphalt.

### TECHNICAL DATA

Nominal Power:	50 W/m
Voltage:	230 Vac
Maximum Exposure Temperature:	250°C
Minimum Install temperature:	-20°C
Dimensions:	6 mm
Circuit Breaker required:	Type C
RCD:	30 mA
Cable Construction:	Mineral Insulated (MI) heating unit with pre-terminated 3 m cold leads.
Certification:	CE, VDE

## RELATED RAYCHEM PRODUCTS

### VIA-DU-20

Programmable ramp heating control with ambient temperature, ground temperature, and moisture sensors.

## PACKAGING AND ORDERING REFERENCES

EM2-MI ramp heating cables are available in the following sizes.

Product name	Order reference	Description
EM2-MI-Pack-26m	075548 – 000	MI Ramp heating element 26 metres
EM2-MI-Pack-36m	772132 – 000	MI Ramp heating element 36 metres
EM2-MI-Pack-48m	625519 – 000	MI Ramp heating element 48 metres
EM2-MI-Pack-60m	375228 – 000	MI Ramp heating element 60 metres
EM2-MI-Pack-70m	686868 – 000	MI Ramp heating element 70 metres
EM2-MI-Pack-88m	268364 – 000	MI Ramp heating element 88 metres

## PRE-INSTALLATION GROUND PREPARATION

The heating cable should be installed on a stable subsurface. In suspended structures the substratum may consist of finished slabs, pre-stressed concrete or a suspended structure with poured concrete. The heating cables can be laid on all sub-surfaces including reinforcement grids/bars. In the case of poured concrete, it should be ensured that the surface is smooth and all sharp objects are removed. Ramps on a solid substratum do not require any additional thermal insulation. Appropriate preparations should be made for installing the temperature and moisture sensor.

## INSTALLATION INSTRUCTION

Complete installation instructions are supplied with the product and are available electronically from Chemelex. Please request installation instruction reference: INST-188.

## SPECIFICATION GUIDELINE

A product specification guideline is available upon request from Chemelex. It is also available online at: [www.chemelex.com](http://www.chemelex.com)

### UK / Ireland

Tel 0800 969 013

SalesUK@chemelex.com