


## RTD temperature sensor for temperature measurement up to 900°F (482°C)

### PRODUCT OVERVIEW



The Raychem RTD4AL is a three-wire platinum RTD (resistance-temperature detector) typically used with monitoring and control systems that require accurate temperature control. The RTD4AL kit can be used with a wide variety of Raychem monitoring and control systems.

### SPECIFICATIONS

Sensor housing & cap	Aluminum A380; TYPE 4X
Sensor sheath	316 stainless steel
Range	-100°F to 900°F (-73°C to 482°C) maximum
Accuracy	±1°F (0.5°C) at 32°F (0°C)
Resistance	100 ohms at 0°C α =0.00385 ohms/ohm/°C
Connection	3/4-in (19 mm) NPT conduit hub <b>Note:</b> The length of RTD extension wires is determined by the wire gauge used. To reduce the likelihood that electrical noise will affect temperature measurement, keep RTD extension wires as short as possible. Use shielded instrument cable such as Raychem MONI-RTD-WIRE (22 AWG, PVC insulation, -30°F to 140°F, -20°C to 60°C) or Belden 83553 (22 AWG, FEP insulation, -95°F to 395°F, -70°C to 200°C).

### ADDITIONAL MATERIALS REQUIRED

Pipe strap, conduit, 16–22 AWG shielded instrument cable

### KIT CONTENTS

One RTD temperature sensor

### APPROVALS

The RTD4AL is CSA certified to U.S. and Canadian standards.



**North America**

Tel +1 800 545 6258

info@chemelex.com



**Raychem Tracer Pyrotenax Nuheat**