

Heat Shrinkable Connection Kits For XL-Trace Edge, Icestop, Raysol And Hwat Self-Regulating Heating Cables

PRODUCT OVERVIEW

- Raychem FTC heat shrinkable connection kits are used with Raychem XL-Trace Edge, IceStop and RaySol self-regulating heating cables.
- Raychem FTC-HST-PLUS connection kits are designed to provide low cost, low profile splice and tee kits.
- Raychem FTC power connection kits can be used for circuit breakers rated up to 40 A.
- Raychem HWT heat shrinkable connection kits are used with Raychem HWAT self-regulating heating cables.
- Raychem HWT power connection kits can be used for circuit breakers rated up to 30 A.

POWERED CONNECTION KITS

Catalog Number	Part Number	Description
FTC-P 	111711-000	Power connection kit with end seal: The FTC-P power connection and end seal kit is for use with XL-Trace Edge, RaySol and IceStop heating cables. Materials for one power connection and end seal is included in the kit.
FTC-XC 	368979-000	Power connection kit with end seal: The FTC-XC power connection and end seal kit is for use with XL-Trace Edge and RaySol heating cables that are run through conduit to a junction box. Materials for one power connection and end seal is included in the kit.
FTC-HST-PLUS 	P000004419	Splice or Tee kit: The FTC-HST-PLUS splice or tee kit is for use with XL-Trace Edge, RaySol, IceStop and HWAT heating cables. Material for two splice or tees included in each kit.
FTC-PSK 	P000000927	Pipe stand and power connection kit: The FTC-PSK pipe stand and power connection kit is for use with XL-Trace Edge heating cables. The stand is designed specifically for the ECW-GF electronic controllers and is compatible with other junction boxes that have 1 inch NPT entries, threaded or non-threaded. Materials for one power connection and end seal is included in the kit.
HWT-P 	P000001664	Power connection kit with end seal: The HWT-P power connection and end seal kit is for use with HWAT heating cables. Materials for one power connection and one end seal are included in this kit.

SPECIFICATIONS

Rated voltage	120–277 V
Maximum circuit breaker size	40 A for FTC and 30A for HWT
Maximum exposure temperature	185°F (85°C) with XL-Trace Edge cable and 150°F (65°C) with IceStop, RaySol and HWAT cables
Minimum installation temperature	0°F (-18°C)
Enclosure rating	NEMA 4X

APPLICABLE PRODUCTS

XL-Trace Edge	3XLE1-CR, 3XLE2-CR, 5/8XLE1-CR/CT and 5/8/12XLE2-CR/CT
IceStop	GM-1XT, GM-1X, GM-2XT and GM-2X
RaySol	RaySol-1 and RaySol-2
HWAT	HWAT-P1 and HWAT-R2

APPROVALS



718K Pipe Heating Cable



Certified with Raysol, IceStop and HWAT heating cables



877Z De-Icing and Snow Melting
Equipment or 9J8 6 Radiant Heating Cable



With IceStop and HWAT heating cables
Excluding FTC-HST-PLUS
Hazardous Locations:
Class I, Div 2. Groups A, B, C, D
GM-1XT and GM-2XT only

DESIGN AND INSTALLATION

For proper design and installation of a FTC or a HWT connection kit, use the appropriate product design guide and the installation instructions included with the connection kit.

GROUND FAULT PROTECTION

To minimize the danger of fire from sustained electrical arcing if the heating cable is damaged or improperly installed, and to comply with the requirements of Chemelex, agency certifications, and national electrical codes, ground fault equipment protection must be used on each heating cable branch circuit. Arcing may not be stopped by conventional circuit protection.

North America

Tel +1 800 545 6258

info@chemelex.com

chemelex
excellence is everything

Raychem Tracer Pyrotenax Nuheat