


LSZH jacketed, copper and alloy 825 sheathed MI cable for freezer frost heave prevention applications


PRODUCT OVERVIEW

MI Heating Cable Configuration


Type SUA Configuration A



Type SUB and FFHP Configuration B



Type FFHPC Configuration D



Types SUA, SUB, and FFHP heating cables have a copper sheath that is extruded with low-smoke zero-halogen (LSZH) jacket and are suitable for applications where the cable is directly embedded in the subfloor.

Type FFHPC heating cables are suitable for applications where the cable is installed in conduit. These heating cables are supplied with a copper sheathed cold lead and a heated length made with either Alloy 825 or a copper sheath with an extruded LSZH jacket.

MI heating cables for frost heave prevention applications are supplied as complete factory fabricated assemblies ready to fasten into a junction box. The copper or Alloy 825 sheath allows for a rugged yet flexible heating cable which is easy to install.

For additional information, contact your Chemelex representative or call (800) 545-6258.

CABLE CONSTRUCTION

Type SUA, SUB and FFHP heating cable

Sheath	Seamless copper
Jacket	LSZH
Insulation	Magnesium oxide
Conductor type	Alloy or copper
Number of conductors	1
Insulation voltage rating	600 V
Cable diameter (with jacket)	0.218 to 0.303 in (5.5 to 7.7 mm)

Type FFHPC heating cable

Sheath	Alloy 825 or seamless copper
Jacket (for copper sheath cables)	LSZH
Insulation	Magnesium oxide
Conductor type	Alloy

CABLE CONSTRUCTION

Number of conductors	2
Insulation voltage rating	300 V
Cable diameter	
Alloy 825 sheath	0.146 to 0.174 in (3.7 to 4.4 mm)
Copper sheath (with jacket)	0.245 to 0.270 in (6.2 to 6.9 mm)
Cold lead	
Sheath	Seamless copper
Jacket (Type SUA/SUB/FFHP cables)	LSZH
Insulation	Magnesium oxide
Conductor type	Copper
Number of conductors	1 or 2
Insulation voltage rating	600 V
Cable diameter	
With jacket	0.320 to 0.430 in (8.1 to 10.9 mm)
Without jacket (Type FFHPC)	0.371 in (9.4 mm)
Gland size (NPT)	1/2 in
Tail length	12 in (30 cm)
Reversed gland size (Type FFHPC)	3/4 in NPT

MINIMUM INSTALLATION TEMPERATURE

Alloy 825-sheathed heating cable	-76°F (-60°C)
LSZH-jacketed heating cable	-4°F (-20°C) for UL, -22°F (-30°C) for CSA

MINIMUM BENDING RADIUS

6 times cable diameter

SUA/SUB HEATING CABLE SPECIFICATIONS

Catalog number	Configuration	Heating cable reference	Heated length		Nominal power (watts)	Cable voltage (volts)	Cold lead length ¹		Cold lead code	Joint type	Nominal heating cable diameter		Resistance ² (ohms)
			(ft)	(m)			(ft)	(m)			(in)	(mm)	
120 Volts and 208 Volts, 3-phase Wye													
SUA3	A	61RD3200-RD	140	42.7	500	120	7	2.1	R22A	Y	0.248	6.3	28.0
SUA4	A	61RD3390-RD	68	20.7	550	120	7	2.1	R22A	Y	0.222	5.6	27.0
SUA7	A	61RD3200-RD	95	29.0	750	120	7	2.1	R22A	Y	0.248	6.3	18.8
SUA8	A	61RE3105-RD	177	53.9	800	120	7	2.1	R22A	Y	0.254	6.5	18.0
SUB1	B	61RE3105-RD	132	40.2	1000	120	15	4.6	R25A	Y	0.254	6.5	14.0
SUB2	B	61RE4600-RD	240	73.1	1000	120	15	4.6	R25A	Y	0.274	7.0	14.5
SUB3	B	61RE4400-RD	280	85.3	1300	120	15	4.6	R30A	Y	0.265	6.7	11.2
SUB4	B	61RE4300-RD	320	97.5	1500	120	15	4.6	R30A	Y	0.272	6.9	9.6
SUB5	B	61RE4300-RD	260	79.2	1800	120	15	4.6	R40A	Y	0.272	6.9	7.9
SUB6	B	61RE4200-RD	375	114.3	1900	120	15	4.6	R40A	Y	0.285	7.2	7.5
SUB7	B	61RE4200-RD	310	94.5	2300	120	15	4.6	R40A	Y	0.285	7.2	6.2
SUB8	B	61RC4100-RD	550	167.6	2300	120	15	4.6	R60A	Y	0.278	7.1	6.4
SUB9	B	61RC5651-RD	630	192.0	3000	120	15	4.6	R60A	Y	0.274	7.0	4.7
SUB10	B	61RC5409-RD	717	218.5	4300	120	15	4.6	R80A	Y	0.303	7.7	3.4
208 Volts													
SUA1	A	61RD3610-RD	108	32.9	650	208	7	2.1	R22A	Y	0.218	5.5	65.9
SUA6	A	61RE3105-RD	264	80.5	1560	208	7	2.1	R22A	Y	0.254	6.5	27.7
SUB19	B	61RD3200-RD	245	74.7	885	208	15	4.6	R25A	Y	0.248	6.3	49.0
SUB20	B	61RE3105-RD	340	103.6	1210	208	15	4.6	R25A	Y	0.254	6.5	35.7

Catalog number	Configuration	Heating cable reference	Heated length		Nominal power (watts)	Cable voltage (volts)	Cold lead length ¹		Cold lead code	Joint type	Nominal heating cable diameter		Resistance ² (ohms)
			(ft)	(m)			(ft)	(m)			(in)	(mm)	
SUB21	B	61RE4600-RD	440	134.1	1640	208	15	4.6	R25A	Y	0.274	7.0	26.5
SUB22	B	61RE4400-RD	525	160.0	2060	208	15	4.6	R25A	Y	0.265	6.7	20.9
240 Volts													
SUB19	B	61RD3200-RD	245	74.7	1175	240	15	4.6	R25A	Y	0.248	6.3	49.0
SUB20	B	61RE3105-RD	340	103.6	1615	240	15	4.6	R25A	Y	0.254	6.5	35.7
SUB21	B	61RE4600-RD	440	134.1	2180	240	15	4.6	R25A	Y	0.274	7.0	26.5
SUB22	B	61RE4400-RD	525	160.0	2745	240	15	4.6	R25A	Y	0.265	6.7	20.9
277 Volts and 480 Volts, 3-phase Wye													
SUB19	B	61RD3200-RD	245	74.7	1565	277	15	4.6	R25A	Y	0.248	6.3	49.0
SUB20	B	61RE3105-RD	340	103.6	2150	277	15	4.6	R25A	Y	0.254	6.5	35.7
SUB21	B	61RE4600-RD	440	134.1	2900	277	15	4.6	R25A	Y	0.274	7.0	26.5
SUB22	B	61RE4400-RD	525	160.0	3650	277	15	4.6	R25A	Y	0.265	6.7	20.9
347 Volts and 600 Volts, 3-phase Wye													
SUB11	B	61RD3390-RD	225	68.6	1400	347	15	4.6	R25A	Y	0.222	5.6	87.8
SUB12	B	61RD3200-RD	310	94.5	1950	347	15	4.6	R25A	Y	0.248	6.3	62.1
SUB13	B	61RE3105-RD	428	130.5	2700	347	15	4.6	R25A	Y	0.254	6.5	45.0
SUB14	B	61RE4600-RD	548	167.0	3700	347	15	4.6	R25A	Y	0.274	7.0	32.7

¹ To modify cold lead length, contact your Chemelex sales representative.

² Resistance tolerance: +/- 10%

Tolerance on heating cable length: -0% to +3%

FFHP HEATING CABLE SPECIFICATIONS

Catalog number	Configuration	Heating cable reference	Heated length		Nominal power (watts)	Cable voltage (volts)	Cold lead length ¹		Cold lead code	Joint type	Nominal heating cable diameter		Resistance ² (ohms)
			(ft)	(m)			(ft)	(m)			(in)	(mm)	
120 Volts and 208 Volts, 3-phase Wye													
FFHP1	B	61RD3610-RD	58	17.7	405	120	15	4.6	R25A	Y	0.218	5.5	35.6
FFHP2	B	61RD3390-RD	72	22.0	510	120	15	4.6	R25A	Y	0.222	5.6	28.2
FFHP3	B	61RD3300-RD	83	25.3	580	120	15	4.6	R25A	Y	0.240	6.1	24.8
FFHP4	B	61RD3200-RD	102	31.1	705	120	15	4.6	R25A	Y	0.248	6.3	20.4
FFHP5	B	61RE3150-RD	117	35.7	820	120	15	4.6	R25A	Y	0.228	5.8	17.6
FFHP6	B	61RE3105-RD	140	42.7	980	120	15	4.6	R25A	Y	0.254	6.5	14.7
FFHP7	B	61RE4800-RD	160	48.8	1125	120	15	4.6	R25A	Y	0.262	6.7	12.8
FFHP8	B	61RE4600-RD	185	56.4	1300	120	15	4.6	R25A	Y	0.274	7.0	11.1
FFHP9	B	61RE4400-RD	226	68.9	1590	120	15	4.6	R25A	Y	0.265	6.7	9.1
FFHP10	B	61RE4300-RD	262	79.9	1830	120	15	4.6	R25A	Y	0.272	6.9	7.9
FFHP11	B	61RE4200-RD	320	97.6	2250	120	15	4.6	R25A	Y	0.285	7.2	6.4
FFHP12	B	61RC4100-RD	426	129.9	2965	120	15	4.6	R30A	Y	0.278	7.1	4.9
FFHP13	B	61RC5651-RD	528	161.0	3675	120	15	4.6	R40A	Y	0.274	7.0	3.9
FFHP14	B	61RC5409-RD	664	202.4	4650	120	15	4.6	R40A	Y	0.303	7.7	3.1
208 Volts													
FFHP15	B	61RD3610-RD	101	30.8	700	208	15	4.6	R25A	Y	0.218	5.5	61.8
FFHP16	B	61RD3390-RD	126	38.4	880	208	15	4.6	R25A	Y	0.222	5.6	49.2
FFHP17	B	61RD3300-RD	144	43.9	1000	208	15	4.6	R25A	Y	0.240	6.1	43.3
FFHP18	B	61RD3200-RD	176	53.7	1230	208	15	4.6	R25A	Y	0.248	6.3	35.2
FFHP19	B	61RE3150-RD	203	61.9	1420	208	15	4.6	R25A	Y	0.228	5.8	30.5
FFHP20	B	61RE3105-RD	243	74.1	1700	208	15	4.6	R25A	Y	0.254	6.5	25.4
FFHP21	B	61RE4800-RD	278	84.8	1945	208	15	4.6	R25A	Y	0.262	6.7	22.2
FFHP22	B	61RE4600-RD	320	97.6	2250	208	15	4.6	R25A	Y	0.274	7.0	19.2

Catalog number	Configuration	Heating cable reference	Heated length		Nominal power (watts)	Cable voltage (volts)	Cold lead length ¹		Cold lead code	Joint type	Nominal heating cable diameter		Resistance ² (ohms)
			(ft)	(m)			(ft)	(m)			(in)	(mm)	
FFHP23	B	61RE4400-RD	394	120.1	2745	208	15	4.6	R25A	Y	0.265	6.7	15.8
FFHP24	B	61RE4300-RD	455	138.7	3170	208	15	4.6	R25A	Y	0.272	6.9	13.7
FFHP25	B	61RE4200-RD	557	169.8	3885	208	15	4.6	R25A	Y	0.285	7.2	11.1
240 Volts													
FFHP26	B	61RD3610-RD	116	35.4	815	240	15	4.6	R25A	Y	0.218	5.5	70.7
FFHP27	B	61RD3390-RD	145	44.2	1020	240	15	4.6	R25A	Y	0.222	5.6	56.5
FFHP28	B	61RD3300-RD	166	50.6	1160	240	15	4.6	R25A	Y	0.240	6.1	49.7
FFHP29	B	61RD3200-RD	203	61.9	1420	240	15	4.6	R25A	Y	0.248	6.3	40.6
FFHP30	B	61RE3150-RD	234	71.3	1640	240	15	4.6	R25A	Y	0.228	5.8	35.1
FFHP31	B	61RE3105-RD	279	85.1	1965	240	15	4.6	R25A	Y	0.254	6.5	29.3
FFHP32	B	61RE4800-RD	320	97.6	2250	240	15	4.6	R25A	Y	0.262	6.7	25.6
FFHP33	B	61RE4600-RD	370	112.8	2600	240	15	4.6	R25A	Y	0.274	7.0	22.2
FFHP34	B	61RE4400-RD	452	137.8	3185	240	15	4.6	R25A	Y	0.265	6.7	18.1
FFHP35	B	61RE4300-RD	522	159.1	3680	240	15	4.6	R25A	Y	0.272	6.9	15.7
FFHP36	B	61RE4200-RD	640	195.1	4500	240	15	4.6	R25A	Y	0.285	7.2	12.8
277 Volts and 480 Volts, 3-phase Wye													
FFHP37	B	61RD3610-RD	134	40.9	940	277	15	4.6	R25A	Y	0.218	5.5	81.6
FFHP38	B	61RD3390-RD	168	51.2	1170	277	15	4.6	R25A	Y	0.222	5.6	65.6
FFHP39	B	61RD3300-RD	191	58.2	1340	277	15	4.6	R25A	Y	0.240	6.1	57.3
FFHP40	B	61RD3200-RD	234	71.3	1640	277	15	4.6	R25A	Y	0.248	6.3	46.8
FFHP41	B	61RE3150-RD	270	82.3	1895	277	15	4.6	R25A	Y	0.228	5.8	40.5
FFHP42	B	61RE3105-RD	322	98.2	2270	277	15	4.6	R25A	Y	0.254	6.5	33.8
FFHP43	B	61RE4800-RD	370	112.8	2590	277	15	4.6	R25A	Y	0.262	6.7	29.6
FFHP44	B	61RE4600-RD	426	129.9	3000	277	15	4.6	R25A	Y	0.274	7.0	25.6
FFHP45	B	61RE4400-RD	525	160.1	3655	277	15	4.6	R25A	Y	0.265	6.7	21.0
FFHP46	B	61RE4300-RD	603	183.8	4240	277	15	4.6	R25A	Y	0.272	6.9	18.1
FFHP47	B	61RE4200-RD	740	225.6	5185	277	15	4.6	R25A	Y	0.285	7.2	14.8
347 Volts and 600 Volts, 3-phase Wye													
FFHP48	B	61RD3610-RD	168	51.2	1175	347	15	4.6	R25A	Y	0.218	5.5	102.5
FFHP49	B	61RD3390-RD	210	64.0	1470	347	15	4.6	R25A	Y	0.222	5.6	81.9
FFHP50	B	61RD3300-RD	239	72.9	1680	347	15	4.6	R25A	Y	0.240	6.1	71.7
FFHP51	B	61RD3200-RD	294	89.6	2050	347	15	4.6	R25A	Y	0.248	6.3	58.7
FFHP52	B	61RE3150-RD	338	103.0	2375	347	15	4.6	R25A	Y	0.228	5.8	50.7
FFHP53	B	61RE3105-RD	405	123.5	2830	347	15	4.6	R25A	Y	0.254	6.5	42.5
FFHP54	B	61RE4800-RD	465	141.8	3240	347	15	4.6	R25A	Y	0.262	6.7	37.2
FFHP55	B	61RE4600-RD	535	163.1	3750	347	15	4.6	R25A	Y	0.274	7.0	32.1
FFHP56	B	61RE4400-RD	655	199.7	4600	347	15	4.6	R25A	Y	0.265	6.7	26.2
FFHP57	B	61RE4300-RD	755	230.2	5315	347	15	4.6	R25A	Y	0.272	6.9	22.7

¹ To modify cold lead length, contact your Chemelex sales representative.

² Resistance tolerance: +/- 10%

Tolerance on heating cable length: -0% to +3%

FFHPC HEATING CABLE SPECIFICATIONS

Catalog number	Configuration	Heating cable reference	Heated length		Nominal power (watts)	Cable voltage (volts)	Cold lead length ¹		Cold lead code	Joint type	Nominal heating cable diameter		Resistance ² (ohms)
			(ft)	(m)			(ft)	(m)			(in)	(mm)	
120 Volts													
FFHPC1	D	32SF2900	15	4.6	105	120	7	2.1	C22A	X	0.160	4.1	137.1
FFHPC2	D	32SA2600	20	6.1	120	120	7	2.1	C22A	X	0.160	4.1	120.0
FFHPC3	D	32SA2400	25	7.6	145	120	7	2.1	C22A	X	0.146	3.7	99.3
FFHPC4	D	32SA2275	30	9.1	175	120	7	2.1	C22A	X	0.153	3.9	82.3
FFHPC5	D	32SA2170	35	10.7	240	120	7	2.1	C22A	X	0.167	4.2	60.0
FFHPC6	D	32SB2114	40	12.2	315	120	7	2.1	C22A	X	0.174	4.4	45.7
FFHPC7	D	32SB2114	45	13.7	280	120	7	2.1	C22A	X	0.174	4.4	51.4
FFHPC8	D	32RD3800-RD	50	15.2	360	120	7	2.1	C22A	Y	0.245	6.2	40.0
FFHPC9	D	32RD3800-RD	55	16.8	330	120	7	2.1	C22A	Y	0.245	6.2	43.6
FFHPC10	D	32RD3600-RD	60	18.3	400	120	7	2.1	C22A	Y	0.255	6.5	36.0
FFHPC11	D	32RD3600-RD	65	19.8	370	120	7	2.1	C22A	Y	0.255	6.5	38.9
FFHPC12	D	32RD3400-RD	70	21.3	515	120	7	2.1	C22A	Y	0.263	6.7	28.0
FFHPC13	D	32RD3400-RD	75	22.9	480	120	7	2.1	C22A	Y	0.263	6.7	30.0
FFHPC14	D	32RD3400-RD	80	24.4	450	120	7	2.1	C22A	Y	0.263	6.7	32.0
FFHPC15	D	32RD3300-RD	85	25.9	565	120	7	2.1	C22A	Y	0.270	6.9	25.5
FFHPC16	D	32RD3300-RD	90	27.4	535	120	7	2.1	C22A	Y	0.270	6.9	26.9
FFHPC17	D	32RE3200-RD	95	29.0	750	120	7	2.1	C22A	Y	0.270	6.9	19.2
FFHPC18	D	32RE3200-RD	100	30.5	720	120	7	2.1	C22A	Y	0.265	6.7	20.0
208 Volts													
FFHPC19	D	32SF1110	25	7.6	155	208	7	2.1	C22A	X	0.130	3.3	279.1
FFHPC20	D	32SF2750	30	9.1	190	208	7	2.1	C22A	X	0.157	4.0	227.7
FFHPC21	D	32SA2600	35	10.7	205	208	7	2.1	C22A	X	0.160	4.1	211.0
FFHPC22	D	32SA2400	40	12.2	270	208	7	2.1	C22A	X	0.146	3.7	160.2
FFHPC23	D	32SA2275	45	13.7	350	208	7	2.1	C22A	X	0.153	3.9	123.8
FFHPC24	D	32SA2275	50	15.2	315	208	7	2.1	C22A	X	0.153	3.9	137.5
FFHPC25	D	32SA2200	55	16.8	390	208	7	2.1	C22A	X	0.169	4.3	110.9
FFHPC26	D	32SA2170	60	18.3	425	208	7	2.1	C22A	X	0.167	4.2	101.8
FFHPC27	D	32SA2170	65	19.8	390	208	7	2.1	C22A	X	0.167	4.2	110.9
FFHPC28	D	32SB2114	70	21.3	540	208	7	2.1	C22A	X	0.174	4.4	80.1
FFHPC29	D	32SB2114	75	22.9	505	208	7	2.1	C22A	X	0.174	4.4	85.7
FFHPC30	D	32SB2114	80	24.4	475	208	7	2.1	C22A	X	0.174	4.4	91.1
FFHPC31	D	32RD3800-RD	85	25.9	635	208	7	2.1	C22A	Y	0.245	6.2	68.1
FFHPC32	D	32RD3800-RD	90	27.4	600	208	7	2.1	C22A	Y	0.245	6.2	72.1
FFHPC33	D	32RD3800-RD	95	29.0	570	208	7	2.1	C22A	Y	0.245	6.2	75.9
FFHPC34	D	32RD3600-RD	100	30.5	720	208	7	2.1	C22A	Y	0.255	6.5	60.1
277 Volts													
FFHPC35	D	32SF1110	30	9.1	230	277	7	2.1	C22A	X	0.130	3.3	333.6
FFHPC36	D	32SF2900	35	10.7	240	277	7	2.1	C22A	X	0.160	4.1	319.7
FFHPC37	D	32SF2750	40	12.2	255	277	7	2.1	C22A	X	0.157	4.0	300.9
FFHPC38	D	32SA2600	45	13.7	285	277	7	2.1	C22A	X	0.160	4.1	269.2
FFHPC39	D	32SA2400	50	15.2	380	277	7	2.1	C22A	X	0.146	3.7	201.9
FFHPC40	D	32SA2400	55	16.8	350	277	7	2.1	C22A	X	0.146	3.7	219.2
FFHPC41	D	32SA2275	60	18.3	465	277	7	2.1	C22A	X	0.153	3.9	165.0

Catalog number	Configuration	Heating cable reference	Heated length		Nominal power (watts)	Cable voltage (volts)	Cold lead length ¹		Cold lead code	Joint type	Nominal heating cable diameter		Resistance ² (ohms)
			(ft)	(m)			(ft)	(m)			(in)	(mm)	
FFHPC42	D	32SA2275	65	19.8	430	277	7	2.1	C22A	X	0.153	3.9	178.4
FFHPC43	D	32SA2275	70	21.3	400	277	7	2.1	C22A	X	0.153	3.9	191.8
FFHPC44	D	32SA2200	75	22.9	500	277	7	2.1	C22A	X	0.169	4.3	153.5
FFHPC45	D	32SA2200	80	24.4	480	277	7	2.1	C22A	X	0.169	4.3	159.9
FFHPC46	D	32SA2170	85	25.9	530	277	7	2.1	C22A	X	0.167	4.2	144.8
FFHPC47	D	32SA2170	90	27.4	500	277	7	2.1	C22A	X	0.167	4.2	153.5
FFHPC48	D	32SB2114	95	29.0	700	277	7	2.1	C22A	X	0.174	4.4	109.6
FFHPC49	D	32SB2114	100	30.5	670	277	7	2.1	C22A	X	0.174	4.4	114.5

1 To modify cold lead length, contact your Chemelex sales representative.

2 Resistance tolerance: +/- 10%

Tolerance on heating cable length: -0% to +3%

Type FFHPC cables supplied with a 3/4 in NPT reversed gland connector and pulling eye.

APPROVALS



FM applies only to the bare copper and stainless steel cable for Freezer Frost Heave installation inside of conduits

GROUND-FAULT PROTECTION

To minimize the danger of fire from sustained electrical arcing if the heating cable is damaged or improperly installed, and to comply with the requirements of Chemelex, agency certifications, and national electrical codes, ground-fault equipment protection must be used on each heating cable branch circuit. Arcing may not be stopped by conventional circuit protection. Many Raychem control and monitoring systems meet the ground-fault protection requirement.

North America

Tel +1 800 545 6258
info@chemelex.com

Latin America

Tel +1 713 868 4800
info@chemelex.com

Europe, Middle East, Africa, India

Tel +32 16 213 511
Fax +32 16 213 604
info@chemelex.com

Asia Pacific

Tel +86 21 2412 1688
infoAPAC@chemelex.com



Raychem Tracer Pyrotenax Nuheat